



THREE-PHASE MOTOR: From 2.7 up to 20 CV (2 / 15 kW)
 230 V-400 V-415 V ; (50/60 HZ)
MONO-PHASE MOTOR: From 2 up to 8 CV (1.5 / 6 kW)
PUMP: From 18 up to 150 L/min.
PRESSURE: From 12 up to 45 BAR

| OIL QUANTITY | |
|-------------------------------------|------------|
| MINIMUM LEVEL | 50 litres |
| USEFUL OIL | 85 litres |
| TOTAL OIL | 135 litres |
| | |
| POWER UNIT WEIGHT WITHOUT OIL | 135 KG |

NOTE:

- DISTRIBUTOR: 15-150 L/1'
- REF TABLE # 9017, TO CHOOSE PUMP AND POWER MOTOR
- OUTLET (*) WITH FLEX-PIPE 1" (M36x2)
- OUTLET (*) WITH FLEX-PIPE 1"1/4 (M45x2)
- AUXILIARY TANK AGAINST POWER UNIT OIL SPILLS (CM320MK2): SEE TAB. 9291
- HEAT EXCHANGER ARRANGEMENT (** OPTIONAL)

| | | | |
|----|--|--|--------------------------|
| UT | | DATA SHEET POWER UNIT CM320-TANK SEALED | DATE 03/20 |
| | | | DWG Nr. 9018/CM320-TS |